

No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0 Casting Resin MS 1000, Hardener (GB)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

Name of product Casting Resin MS 1000, Hardener (GB)

Code-Nr. 105202

Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Hardener Component

Details of the supplier of the safety data sheet

Manufacturer/distributor WEICON GmbH & Co. KG

Königsberger Straße 255, DE-48157 Münster

Postbox 84 60, DE-48045 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244

E-Mail: info@weicon.de Internet: www.weicon.de

Advice Abteilung Angebote, Verkauf, Export

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

info@weicon.de

**Emergency telephone number** 

Emergency advice Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)

Phone ++49(0)228-19 240

# **SECTION 2: Hazards identification**

Classification of the substance or mixture

### Classification according to 67/548/EEC or 1999/45/EC

Xi; R38 Xi; R41 R43 R52/53 **R-phrases** 

38 Irritating to skin.

41 Risk of serious damage to eyes.

43 May cause sensitisation by skin contact.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# Label elements

### Labelling according to 67/548/EEC or 1999/45/EC

### Remarks for labelling

The product is classified and labelled in accordance with EC directives.

Xi Irritant

R-phrases

38 Irritating to skin.

41 Risk of serious damage to eyes.

43 May cause sensitisation by skin contact.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

2 Keep out of the reach of children.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0 Casting Resin MS 1000, Hardener (GB)

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

46 If swallowed, seek medical advice immediately and show this container or label.
61 Avoid release to the environment. Refer to special instructions/safety data sheets.

### Hazardous ingredients for labeling

3,6-diazaoctanethylenediamin

Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

#### **Mixtures**

### **Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
112-24-3	203-950-6	3,6-diazaoctanethylenediamin	22-30	Xn R21; C R34; R43; R52-53
CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
112-24-3	203-950-6	3,6-diazaoctanethylenediamin	22-30	Acute Tox. 4, H312 / Skin Corr. 1B, H314 / Skin

#### Description

Modified aliphatic polyamine.

## **SECTION 4: First aid measures**

# Description of first aid measures

## **General information**

Remove contaminated soaked clothing immediately.

# In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

# In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

# In case of eye contact

In case of contact with eyes rinse thoroughly with water.

Call for a doctor immediately.

### In case of ingestion

Do not induce vomiting.

If swallowed give water to drink.

# Most important symptoms and effects, both acute and delayed

No information available.

### Indication of any immediate medical attention and special treatment needed

No information available.

# **SECTION 5: Firefighting measures**

# **Extinguishing media**

### Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0 Casting Resin MS 1000, Hardener (GB)

### Extinguishing media which must not be used for safety reasons

Full water jet

#### Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

### Advice for firefighters

#### Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

### **SECTION 6: Accidental release measures**

## Personal precautions, protective equipment and emergency procedures

Remove persons to safety.

Keep away sources of ignition.

### **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

### Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Send in suitable containers for recovery or disposal.

#### Reference to other sections

No information available.

# **SECTION 7: Handling and storage**

### Precautions for safe handling

# Advice on safe handling

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Take precautionary measures against static discharges.

# Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep in closed original container.

# Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

# Further information on storage conditions

Storage temperature between 2°C to 40°C

#### Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

#### **Control parameters**

No information available.

#### **Exposure controls**

# **Respiratory protection**

If ventilation insufficient, wear respiratory protection.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0 Casting Resin MS 1000, Hardener (GB)

### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves. Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

#### Eye protection

tightly fitting goggles protective shield

### Skin protection

Light protective clothing. Safety shoes.

# **General protective measures**

Avoid contact with eyes and skin Do not inhale gases/vapours/aerosols.

### Hygiene measures

Do not smoke when working. At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

# **SECTION 9: Physical and chemical properties**

Information on basic physical and chemical properties

Form Colour Odour liquid clear similar to amine

### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value in delivery state	ca. 12	20			1:1 in water
boiling point (decomposition)	> 200 °C				
Flash point	152 °C			DIN 51758	
Vapour pressure	0,1 Pa	20 °C			
Density	1-1,05 g/cm3	25 °C			
Solubility in water					miscible
Viscosity dynamic	370 - 470 mPa*s	25 °C			

# Other information

No information available.

# **SECTION 10: Stability and reactivity**

## Reactivity

No information available.

# **Chemical stability**

No information available.

# Possibility of hazardous reactions

No information available.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0 Casting Resin MS 1000, Hardener (GB)

### Conditions to avoid

Keep away from heat.

#### Incompatible materials

#### Materials to avoid

Reactions with strong acids and alkalies. Reactions with strong oxidising agents.

### **Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx) Toxic gases/vapours

# **SECTION 11: Toxicological information**

# Information on toxicological effects

## Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	4500 mg/kg	rat		
LD50 acute dermal	> 2150 mg/kg	rat		
Irritability skin	irritant		OECD 404	
Irritability eye	irritant - risk of strong eye injuries		OECD 405	
Skin sensitization	sensitizing	Guinea pig		

#### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

# **SECTION 12: Ecological information**

## **Toxicity**

No information available.

### Persistence and degradability

No information available.

# **Bioaccumulative potential**

No information available.

## Mobility in soil

No information available.

# Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

Other adverse effects

# **General regulation**

Do not allow uncontrolled leakage of product into the environment. Product is not allowed to be discharged into aquatic environment.



No. 1907/2006 (REACH) Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0 Casting Resin MS 1000, Hardener (GB)

### **SECTION 13: Disposal considerations**

Waste treatment methods

Waste code No. Name of waste

07 02 04\* other organic solvents, washing liquids and mother liquors

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

### Recommendations for packaging

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

# **SECTION 14: Transport information**

#### Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

## Special precautions for user

No information available.

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

# **SECTION 15: Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **VOC** standard

#### Remark

Daten separat anfragen / Request data separately.

# **Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

#### **Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

# Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 21 Harmful in contact with skin.

R 34 Causes burns.

R 43 May cause sensitisation by skin contact.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.