

W 44 T® Multi-Spray



multifunctional oil with multiple effects

WEICON W 44 T® is a multifunctional product which, thanks to its special formula and outstanding creeping capacity, combines corrosion protection, water displacement, lubrication, conservation and cleaning in a single product.

WEICON W 44 T® loosens seized threads, bolts, fittings and valves, penetrates and dissolves rust, dispels moisture from electrical contacts, prevents tracking currents and makes it easier to start wet motors.

W 44 T can also be used as cutting oil for drilling and cutting processes.

It eliminates squeaky and creaky noises on hinges, guides, bearings and all types of joints and couplings. It cleans soiled metal surfaces and leaves a long-lasting razorthin film which doesn't smear or stick and does not attract dust. It protects and preserves all types of tools, machines, and electrical and mechanical precision devices and keeps them functional. The use of WEICON W 44 T® has almost no limitations in workshop, automotive, shipping, electrical, agricultural, household and hobby applications.

Technical Data

Odour	vanilla
Features	multifunctional oil with multiple effect
Silicone free	yes
Storage stability	24 months
Colour	yellowish
Kinematic viscosity (DIN 51562) at +40°C	21 mm²/s
Kinematic viscosity (DIN 51562) at +100°C	4 mm²/s
Temperature resistance	-50 to +210 °C
ISSA-Code	53.402.11
IMPA-Code	45 08 21

Processing

Shake can before use. Spray W 44 T on evenly and at about 5 cm distance from surface and allow to react for 30 seconds.

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding $+50^{\circ}$ C.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

11251050	W 44 T® Multi-Spray 50 ml
11251200	W 44 T® Multi-Spray 200 ml
11251400	W 44 T® Multi-Spray 400 ml
11251550	W 44 T® Multi-Spray 500 ml

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.