

No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Casting Resin MS 1000, Resin (GB)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product Casting Resin MS 1000, Resin (GB)

Code-Nr. 105201

Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

Details of the supplier of the safety data sheet

Manufacturer/distributor WEICON GmbH & Co. KG

Königsberger Straße 255, DE-48157 Münster

Postbox 84 60, DE-48045 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244

E-Mail: info@weicon.de Internet: www.weicon.de

Advice Abteilung Angebote, Verkauf, Export

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

info@weicon.de

Emergency telephone number

Emergency advice Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)

Phone ++49(0)228-19 240

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to 67/548/EEC or 1999/45/EC

Xi; R36/38 R43 N; R51/53 **R-phrases**

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Label elements

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

Xi Irritant

N Dangerous for the environment

R-phrases

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

2 Keep out of the reach of children.

After contact with skin, wash immediately with plenty of water and soap.

37/39 Wear suitable gloves and eye/face protection.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Casting Resin MS 1000, Resin (GB)

If swallowed, seek medical advice immediately and show this container or label.
Avoid release to the environment. Refer to special instructions/safety data sheets.

Hazardous ingredients for labeling

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. See information supplied by the manufacturer.

Other hazards

No information available.

SECTION 3: Composition/information on ingredients

Mixtures

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC	
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	70 - 82	Xi R36/38; R43; N R51-53	
CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]	
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	70 - 82	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411	
REACH					
CAS No	Name			REACH registration number	
25068-38-6	reaction proc molecular we	luct: bisphenol-A-(epichlorhydrin) epoxy resin (number bight <= 700)	average	01-2119456619-26-xxxx	

Description

Modified bisphenol-A-epoxy resin

SECTION 4: First aid measures

Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Give activated charcoal.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Give plenty of water to drink in small sips.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Casting Resin MS 1000, Resin (GB)

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide Water spray jet

_

Extinguishing media which must not be used for safety reasons

Full water jet

Special hazards arising from the substance or mixture

Dense, black smoke,

Fire gas of organic material has to be classed invariably as respiratory poison.

Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Burns down under strong soot production.

Collect contaminated firefighting water separately, must not be discharged into the drains.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove persons to safety.

Use personal protective clothing.

Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Send in suitable containers for recovery or disposal.

Reference to other sections

No information available.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace. Open and handle container with care!

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.



No. 1907/2006 (REACH) Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Casting Resin MS 1000, Resin (GB)

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Further information on storage conditions

Storage temperature between 2°C to 40°C

Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

Control parameters

No information available.

Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves. Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

tightly fitting goggles protective shield

Skin protection

Light protective clothing. Safety shoes.

General protective measures

Avoid contact with eyes and skin Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Form Colour Odour

liquid light yellow hardly noticeable

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value in delivery state	ca. 7	20			1:1 in water
boiling point	> 200 °C				
Flash point	> 200 °C			DIN 51758	
Vapour pressure	< 0,01 Pa	20 °C			
Density	1,1 g/cm3	25 °C		DIN 51757	
Solubility in water					insoluble
Viscosity dynamic	1250 - 1600 mPa*s	25 °C			



No. 1907/2006 (REACH) Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Casting Resin MS 1000, Resin (GB)

Method

Remark

Other information

No information available.

SECTION 10: Stability and reactivity

Reactivity

No information available.

Chemical stability

No information available.

Possibility of hazardous reactions

No information available.

Conditions to avoid

No information available.

Incompatible materials

Materials to avoid

Reactions with strong oxidising agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide. risk of formation of toxic pyrolysis products

Thermal decomposition

Remark thermal decomposition >200°C

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity/Irritability/Sensitization

	Value/Validation	Species
LD50 acute oral	> 5000 mg/kg	rat
Irritability skin	irritant	rabbit
Irritability eye	irritant	rabbit eye
Skin sensitization	sensitizing	Guinea pig

Experiences made from practice

Sensitization through skin contact possible.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information

Toxicity

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Casting Resin MS 1000, Resin (GB)

No information available.

Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Waste code No.

Name of waste

07 02 08*

other still bottoms and reaction residues

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land and inland navigation transport ADR/RID

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY HARZ), 9, III, (E), Classification code: M6

transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN), 9, III

MARINE POLLUTANT: Yes

Air transport ICAO/IATA-DGR

UN 3082 Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN), 9, III

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

Special precautions for user

No information available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

Remark

Daten separat anfragen / Request data separately.

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



No. 1907/2006 (REACH) Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Casting Resin MS 1000, Resin (GB)

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.