

No. 1907/2006 (REACH) Printed 29.09.2009

Revision 20.09.2009 (GB) Version 5.5

WEICONLOCK AN 302-42 (GB)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Name of product WEICONLOCK AN 302-42 (GB)

Code-Nr. 30242

Manufacturer/distributor WEICON GmbH & Co. KG

Königsberger Straße 255, DE-48157 Münster

Postbox 84 60, DE-48045 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244

E-Mail: info@weicon.de Internet: www.weicon.de

Advice Abteilung Angebote, Verkauf, Export

Phone ++49(0)251 / 9322 - 0

Emergency advice Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)

Phone ++49(0)228-19 240

Recommended intended purpose(s)

1-Component Adhesives and Sealants, anaerobic curing

2. HAZARDS IDENTIFICATION

Classification

Xi; R36/37/38

R-phrases

36/37/38 Irritating to eyes, respiratory system and skin.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization

Anaerobic adhesive / sealant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification
80-15-9	201-254-7	cumene hydroperoxide	1	O R7; T R23; Xn R21/22-48/20/22; C R34; N R51-53
27813-02-1	248-666-3	methyl acrylic acid ester	> 10	Xi R36/37/38

4. FIRST AID MEASURES

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.



No. 1907/2006 (REACH) Printed 29.09.2009

Revision 20.09.2009 (GB) Version 5.5

WEICONLOCK AN 302-42 (GB)

If swallowed give water to drink.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

sand

Water spray jet

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Fire gas of organic material has to be classed invariably as respiratory poison.

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Ensure adequate ventilation.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods for cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

7. HANDLING AND STORAGE

Further information on storage conditions

Store only in original container at temperature of 28°C maximum (=80°F).

Protect from direct solar radiation.

Keep cool.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

safety goggles

General protective measures

Avoid contact with eyes and skin

Hygiene measures

Wash hands before breaks and after work.

Use barrier skin cream.



No. 1907/2006 (REACH) Printed 29.09.2009

Revision 20.09.2009 (GB) Version 5.5

WEICONLOCK AN 302-42 (GB)

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Colour Odour

verschiedene various hardly noticeable

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value in delivery state	4-6				
Flash point	> 100 °C			DIN/ISO 2592	
Autoignition	> 380 °C				
Vapour pressure	< 5 mbar	20 °C		DIN 51616	
Density	1-1,1 g/ml	20 °C		DIN 51757	
Solubility in water		20 °C			more or less insoluble
Viscosity 1 dynamic	500-100000 mPa*s	25 °C		Brookfield-Visk.	

10. STABILITY AND REACTIVITY

Conditions to avoid

Keep away from heat.

Materials to avoid

Reactions with metals.

Reactions with strong acids and alkalies.

Reactions with strong oxidising agents.

Hazardous decomposition products

carbon monoxide and carbon dioxide

Nitrous oxides (NOx)

Additional information

Polymerization at temperatures exceeding 100°C

11. TOXICOLOGICAL INFORMATION

Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
LD 50 acute oral	> 5000 mg/kg	rat		
Irritability skin	irritant			
Irritability eye	irritant			



No. 1907/2006 (REACH)
Printed 29.09.2009

Revision 20.09.2009 (GB) Version 5.5

WEICONLOCK AN 302-42 (GB)

12. ECOLOGICAL INFORMATION

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

13. DISPOSAL CONSIDERATIONS

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

14. TRANSPORT INFORMATION

Transport/further information

No hazardous material as defined by the prescriptions.

15. REGULATORY INFORMATION

Remarks for classification

The product is classified and labelled in accordance with EC directives.

Classification

Xi Irritant

R-phrases

36/37/38 Irritating to eyes, respiratory system and skin.

S-phrases

2 Keep out of the reach of children.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

46 If swallowed, seek medical advice immediately and show this container or lable.

16. OTHER INFORMATION

Recommendend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R-phrases specified in chapter 3 (not the classification of the formulation!)

R 21/22 Harmful in contact with skin and if swallowed.

R 23 Toxic by inhalation.

R 34 Causes burns.

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 48/20/22 Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 7 May cause fire.